



ROUNDIT product range		Material sample
	<p><b>Roundit 2000 NX</b> Specification: EN 6049-006 / BMS 13-81 · 200 °C Sizes: 5 – 40 mm (3/16 – 1 1/2") · Mechanical protection - Bundling</p>	
Mechanical Protection	<p><b>Roundit 2000 NX Ptr &amp; Vtr</b> Specification: S8021 · 200 °C · Sizes: 5 – 40 mm (3/16 – 1 1/2") Identification - Fuel tank wire harnesses (Ptr), Fiber optic harnesses (Vtr)</p>	
	<p><b>Roundit 2000 NX Red &amp; Orange</b> Specification: EN 6049-006 · 200 °C · Sizes: 5 – 40 mm (3/16 – 1 1/2") Identification - Weapon systems (Red), FTI (Orange)</p>	
	<p><b>Roundit 2000 LX</b> Specification: 200 °C · Sizes: 5 – 42 mm (3/16 – 1 1/2") Mechanical protection - Bundling</p>	
	<p><b>Roundit PPS</b> Specification: ABS 1552 · 200 °C · Sizes: 5 – 38 mm (3/16 – 1 1/2") Mechanical protection for metallic shields and SWAMP areas</p>	
	<p><b>Roundit 2000 NX HT</b> Specification: EN 6049-007 · 260 °C · Sizes: 5 – 40 mm (3/16 – 1 1/2") Mechanical protection - Bundling - Electrical insulation</p>	
Thermal & Fire Protection	<p><b>RounditTherm A</b> Specification: EN 6049-009 · 260 °C · Sizes: 10 – 30 mm (3/8 – 1 1/4") Fire protection - Five minutes ISO2685</p>	
	<p><b>Therm-L-Wrap 66</b> Specification: 200 °C · Sizes: 10 – 25 mm (3/8 – 1") Thermal radiant heat protection</p>	
EMI Shielding	<p><b>Roundit EMI FMJ</b> Specification: MPS QTM.MPS.JPB.10.17 · 200 °C · Sizes: 8 – 38 mm (5/16 – 1 1/2") · Mechanical protection - EMI shielding</p>	
	<p><b>Roundit 2000 NX EMI</b> Specification: EN 6049-008 · 200 °C · Sizes: 6 – 38 mm (1/4 – 1 1/2") Mechanical protection and EMI shielding, Internal protection of wire harnesses</p>	

